



FEMALE INSULATED DISCONNECTOR

Key Features:

- The female disconnecter is a terminal to used to connect wires to appliances and devices with a male terminus.
- Provide a quick and reliable solderless electrical connection

Materials/Finish:

- Terminals are made from electrolytic copper, rolled tin-plated and brazed high quality Nylon/PVC insulation are used which are able to withstand high duress resulting from crimping



Type	Wire Range (mm ²)	DIMENSIONS (MM)						Colour
		W	L	t	φd	φD	B	
RF110-5	1.5	3.2	18.5	0.3	1.8	3.8	10	RED
RF110-8	1.5	3.2	18.5	0.3	1.8	3.8	10	RED
RF187-5	1.5	5	19	0.4	1.8	3.8	10	RED
RF187-8	1.5	5	19	0.4	1.8	3.8	10	RED
RF250	1.5	6.6	20.3	0.4	1.8	3.8	10	RED
BF110-5	2.5	3.2	18.5	0.3	2.4	4.2	10	BLUE
BF110-8	2.5	3.2	18.5	0.3	2.4	4.2	10	BLUE
BF187-5	2.5	5	19	0.4	2.4	4.2	10	BLUE
BF187-8	2.5	5	19	0.4	2.4	4.2	10	BLUE
BF250	2.5	6.6	20.3	0.4	2.4	4.2	10	BLUE
YF110-5	4-6.0	3.2	22	0.4	3.5	5.4	13	YELLOW
YF110-8	4-6.0	3.2	22	0.4	3.5	5.4	13	YELLOW
YF187-5	4-6.0	5	22	0.4	3.5	5.4	13	YELLOW
YF187-8	4-6.0	5	22	0.4	3.5	5.4	13	YELLOW
YF250	4-6.0	6.6	23.3	0.4	3.5	5.4	13	YELLOW

