



INSULATED CORD-END TERMINAL

Insulated cord end terminal use to terminate the end of a cable and are widely used in electrical applications.



ITEM NO	WIRE RANGE	DIMENSIONS(mm)						COLOR
	(mm ²)	D1	D2	L	L1	S1	S2	
LT02508	0.25	0.75	1.9	12	8	0.15	0.3	LIGHT BLUE
LT05006	0.5	1	2.6	12	6	0.15	0.3	ORANGE
LT05008	0.5	1	2.6	14	8	0.15	0.3	ORANGE
LT05010	0.5	1	2.6	16	10	0.15	0.3	ORANGE
LT07506	0.75	1.2	2.8	12	6	0.15	0.3	WHITE
LT07508	0.75	1.2	2.8	14	8	0.15	0.3	WHITE
LT07510	0.75	1.2	2.8	16	10	0.15	0.3	WHITE
LT07512	0.75	1.2	2.8	18	12	0.15	0.3	WHITE
LT10006	1	1.4	3	12	6	0.15	0.3	YELLOW
LT10008	1	1.4	3	14	8	0.15	0.3	YELLOW
LT10010	1	1.4	3	16	10	0.15	0.3	YELLOW
LT10012	1	1.4	3	18	12	0.15	0.3	YELLOW
LT15008	1.5	1.7	3.5	14	8	0.15	0.3	RED
LT15010	1.5	1.7	3.5	16	10	0.15	0.3	RED
LT15012	1.5	1.7	3.5	18	12	0.15	0.3	RED
LT25008	2.5	2.2	4.2	14	8	0.15	0.3	BLUE
LT25010	2.5	2.2	4.2	16	10	0.15	0.3	BLUE
LT25012	2.5	2.2	4.2	18	12	0.15	0.3	BLUE
LT40010	4	2.8	4.8	18	10	0.2	0.35	GREY
LT40012	4	2.8	4.8	20	12	0.2	0.35	GREY
LT60012	6	3.5	6.3	20	12	0.2	0.4	BLACK
LT100012	10	4.5	7.6	20	12	0.2	0.4	IVORY
LT160012	16	5.8	8.8	24	12	0.2	0.4	GREEN
LT250016	25	7.3	11.2	30	16	0.2	0.4	BROWN
LT350016	35	8.3	12.7	30	16	0.2	0.4	BEIGE
LT500020	50	10.3	15	36	20	0.3	0.5	OLIVE
LT700021	70	13.5	16	37	21	0.4	0.6	YELLOW
LT950025	95	14.7	18	44	25	0.4	0.6	RED
LT120027	120	16.7	20	48	27	0.45	0.7	BLUE

