



Intelligent Large Screen Digital Multimeter VC923E

Auto Intelligent, True RMS, Audible and visual alarm, NCV, Status Bar Display, Data Retention, Key switching, Gear Display, Automatic Shutdown, 599 bit display, Low voltage prompt, Reminder of fuse burning out, Inbuilt Flashlight, Live wire detection, Prompt Light, Over range prompt



Function	Range	Accuracy
DC voltage	600mV/6V/60V600V	±(0.5%+3)
AC voltage	6V/60V/600V	±(1.0%+3)
DC current	600mA/6A/10A	±(1.2%+3)
AC current	600mA/6A/10A	±(1.2%+3)
Resistance	6000/6kΩ/60kΩ /600kΩ/6MΩ	±(1.0%+5)
	60MQ	±(2%+10)
	6nF/60nF/600nF /6uF/60uF/600uF	±(4%+5)
Capacitance	6mF	±(5%+5)
	60mF	±(10%+10)
Frequency	6Hz/60Hz/600Hz/6kHz/60kHz/ 600kHz/6MHz/10MHz	±(1.0%+3)
Temperature	(-40~1000)C or (-40~1832)°F	+3°F

Essential Information

LCD display	5999 max	Work environment	0-40°C(<75%RH)
Overload	OL	Storage	-20-60°C(<85%RH)
Alarm signal	Audible and visual alarm	Jack prompt	V
Power	1.5V AAA*4	NCV	V
Low voltage	V	Flashlight	V
Auto shutdown	No operation for 15 minutes	Data retention	V
Size	144*73*27 mm	Diode	V
Weight	About 235g	On off buzzer	V