

9" RATCHET CRIMPING TOOL

HS-30J

- The components of the tool are made of special steel which comprise of rustproof features
- Adheres to strict testing which conforms to international standard prior to delivery
- Intricately designed crimping dies set and self-releasing integral locking mechanism ensures high quality crimping effect, even after long usage



Specifications

| | |
|-------------|----------------------|
| Capacity | 0.5-6mm ² |
| AWG | 22-10 |
| Length (mm) | 230 |
| Weight (kg) | 0.6 |

HS-101

For non-insulated terminals



Specifications

| | |
|-------------|-----------------------|
| Capacity | 1.5-10mm ² |
| AWG | 16-8 |
| Length (mm) | 230 |
| Weight (kg) | 0.6 |

HS-03B

For non-insulated tabs and receptacles




Specifications

| | |
|-------------|----------------------|
| Capacity | 1.5-6mm ² |
| AWG | 16-10 |
| Length (mm) | 230 |
| Weight (kg) | 0.6 |

9" RATCHET CRIMPING TOOL

HS-07FL

For 1.5/2.5mm² Flag Type female receptacles insulated terminal




Specifications

| | |
|-------------|----------------------|
| Capacity | 0.5-6mm ² |
| AWG | 22-10 |
| Length (mm) | 230 |
| Weight (kg) | 0.6 |

HS-05FL/06FL

For 4.8/6.3mm² Flag Type receptacles




Specifications

| | |
|-------------|--|
| Capacity | 0.5-1.5mm ² 1.5-2.5mm ² |
| AWG | 20-14 |
| Length (mm) | 230 |
| Weight (kg) | 0.6 |

HS-05WF

For insulated and non-insulated ferrules




Specifications

| | |
|-------------|----------------------|
| Capacity | 0.5-6mm ² |
| AWG | 20-10 |
| Length (mm) | 203 |
| Weight (kg) | 0.4 |

HS-103

For insulated closed end terminals



Specifications

| | |
|-------------|-----------------------|
| Capacity | 1.5-10mm ² |
| AWG | 16-8 |
| Length (mm) | 230 |
| Weight (kg) | 0.6 |

9" RATCHET CRIMPING TOOL

HS02H1

For RG55, 58, 59,62, 140, 141, 142, 223, 303, 400, Fiber Optic, Belden 8279




Specifications

| | |
|-------------|------------------------|
| Capacity | 1.0-6.5mm ² |
| AWG | - |
| Length (mm) | 230 |
| Weight (kg) | 0.6 |

HS2546B

Solar Connector



Specifications

| | |
|-------------|----------------------------|
| Capacity | 2, 5, 4, 6 mm ² |
| AWG | 13-10 |
| Length (mm) | 230 |
| Weight (kg) | 0.52 |

HS-HT4

For insulated and non-insulated ferrules



Specifications

| | |
|-------------|----------------------|
| Capacity | 0.5-6mm ² |
| AWG | 20-10 |
| Length (mm) | 203 |
| Weight (kg) | 0.4 |

HS35WF

For insulated and non-insulated ferrules



Specifications

| | |
|-------------|-------------------------------|
| Capacity | 10, 16, 25, 35mm ² |
| AWG | 8-2 |
| Length (mm) | 230 |
| Weight (kg) | 0.52/0.56 |