

9" RATCHET CRIMPING TOOL

HS-30J

- The components of the tool are made of special steel which comprise of rustproof features
- Adheres to strict testing which conforms to international standard prior to delivery
- Intricately designed crimping dies set and self-releasing integral locking mechanism ensures high quality crimping effect, even after long usage



Specifications

Capacity	0.5-6mm ²
AWG	22-10
Length (mm)	230
Weight (kg)	0.6

HS-101

For non-insulated terminals



Specifications

Capacity	1.5-10mm ²
AWG	16-8
Length (mm)	230
Weight (kg)	0.6

HS-03B

For non-insulated tabs and receptacles



Specifications

Capacity	1.5-6mm ²
AWG	16-10
Length (mm)	230
Weight (kg)	0.6

9" RATCHET CRIMPING TOOL

HS-07FL

For 1.5/2.5mm² Flag Type female receptacles insulated terminal




Specifications

Capacity	0.5-6mm ²
AWG	22-10
Length (mm)	230
Weight (kg)	0.6

HS-05FL/06FL

For 4.8/6.3mm² Flag Type receptacles



Specifications

Capacity	0.5-1.5mm ² 1.5-2.5mm ²
AWG	20-14
Length (mm)	230
Weight (kg)	0.6

HS-05WF

For insulated and non-insulated ferrules



Specifications

Capacity	0.5-6mm ²
AWG	20-10
Length (mm)	203
Weight (kg)	0.4

HS-103

For insulated closed end terminals



Specifications

Capacity	1.5-10mm ²
AWG	16-8
Length (mm)	230
Weight (kg)	0.6

9" RATCHET CRIMPING TOOL

HS02H1

For RG55, 58, 59, 62, 140, 141, 142, 223, 303, 400,
Fiber Optic, Belden 8279



Specifications

Capacity	1.0-6.5mm ²
AWG	-
Length (mm)	230
Weight (kg)	0.6

HS2546B

Solar Connector



Specifications

Capacity	2, 5, 4, 6 mm ²
AWG	13-10
Length (mm)	230
Weight (kg)	0.52

HS-HT4

For insulated and non-insulated ferrules



Specifications

Capacity	0.5-6mm ²
AWG	20-10
Length (mm)	203
Weight (kg)	0.4

HS35WF

For insulated and non-insulated ferrules



Specifications

Capacity	10, 16, 25, 35mm ²
AWG	8-2
Length (mm)	230
Weight (kg)	0.52/0.56